SONY

like.no.other™

MDR-RF850RK

Category	Wireless headphones
Subcategory	RF
General data	
Type	Closed, dynamic
Driver unit	30 mm
Diaphragm	PET
Magnet	Ferrite
Frequency response	10-22.000 Hz
Volume control	Rotary
Tuning	Automatic
Auto ON/OFF function	Power turns ON automatically when headphones are worn
Power ON indicator	LED

Mute function	Volume level decreases when RF signal is weak or not received
Headband	Wide single headband with self adjusting mechanism
Wearing style	Circum aural
Weight of headphones	Approx. 270 g. (incl. batt.)
Recharging time	Approx. 16 H (from 0 to full)
Supplied battery type / life	Ni-MH x 2 / 15H (when fully charged)
Optional battery type / life	AAA x 2 / 24H
Battery note	Rechargeable battery can be replaced by normal AAA battery (x 2)
Transmitter / Charger	
Charging stand type	Standing headphone charger
Charging method	Autom. charged by placing headphone on the transmitter
Audio input options	Stereo mini jack / RCA - jack
Battery charge indication	Green LED on lights up when the battery is charged
	Red LED lights up on the headphones and transmitter when the power is ON
Power ON indicator	DC 9V from the supplied
Power source	AC adaptor
Modulation	AFM transmission system
Signal range (reception area)	Up to 100 m
Available channels	3 (for optimum signal reception)
Channel selection method	Slide witch (CH1, CH2, CH3)
Transmitting frequency	Channel 1: 863.5 MHz, channel 2: 864.0 MHz, channel 3: 864.5 MHz
Transmitter frequency range	20-15.000 Hz
Transmitter power ON/OFF	Signal transmission starts when audio signal is detected
Dimensions (WxHxD) in mm	133x124x136
Weight of transmitter	Approx. 195 g.
Supplied accessories	
	AC power adaptor (9V)
	Rechargeable battery (Ni-MH) (BP-HP550)
	Connecting cord (1m, 1 stereo mini plug <-> 2 phone plugs)
Package	Unimatch plug adaptor (stereo mini plug <-> stereo phone plug)
Style	Box
Dimensions (WxHxD in cm)	21x30x15
Package per Carton	4